# Trend I A Class



The bestseller in the Dethleffs model programme has been completely revised: Modern design, extensive standard equipment and practical new functions make the Trend the undisputed price/performance winner. A special comfort feature is the stepless IsoProtect living area floor, which extends from the driver's cab to the bathroom. With the large pull-down bed in the driver's cab, there are always two additional, comfortable sleeping berths on board the Trend Integrated as standard, which do not take up any space during the day.

Technical info	
Overall length, approx.	670 - 740 cm
Overall width, approx.	233 cm
Overall height, approx.	300 cm
Headroom in living area, approx.	205 cm

Maximum values partly not possible for all models or only in connection with certain options.

## Upholstery



+ Upholstery Saros



+ Upholstery Yoko



+ Upholstery Heron (partial textileleather) O

## Plus factors

- Lifetime Smart superstructure with wood-free, GRPclad underbody
- Exclusive rear design with top-entry rear wall,
   ShapeLine LED tail lights and 3rd brake light integrated into the rear spoiler
- + Large rear garage can be loaded on both sides, onehand operation of the garage doors, lighting, 230 V socket and sturdy lashing rails
- + 70 cm wide habitation door with convenient coupe entrance
- + Level Iso-Protect comfort flooring in the living area without landings or steps
- New overhead locker concept with handleless fronts and large storage volume incl. AirPlus overhead locker rear ventilation
- + Pull-down bed in the cab as standard
- + Sleeping area: Outstanding sleeping comfort with 150 mm thick Evopore cold foam mattresses

### Wood décor



+ Wood décor Ashton

O optionally available



















## Trend I A Class Technical info







Trend I A Class		I 6617 EB	I 6817 EB	I 6877
Standard chassis		Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform
Emission standards		Euro 6e	Euro 6e	Euro 6e
Overall length, approx.	cm	670	699	699
Overall width, approx.	cm	233	233	233
Overall height, approx.	cm	300 1)	300 1)	300 <sup>1)</sup>
Headroom in living area, approx.	cm	205	205	205
Towable load braked/unbraked	kg	2000 / 750	2000 / 750	2000 / 750
Wheelbase, approx.	mm	3800	3800	3800
Bed dimension: Front bed, L x W, approx.	cm	196 x 150	196 x 150	196 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm			210 x 118 - 80 O
Bed dimension: Rear bed, L x W, approx.	cm	212 x 80 / 201 x 80 / 211 x 144	207 x 80 / 194 x 80 / 211 x 192	212 x 162
Sleeping berths standard / max.		4	4	4/50
Standard engine		140 MultiJet 3	140 MultiJet 3	140 MultiJet 3
kW (bhp)		103 (140)	103 (140)	103 (140)
Mass in running order (+/-5%)*	kg	2912 (2766 to 3058)*	2931 (2784 to 3078)*	2974 (2825 to 3123)*
Manufacturer-specified mass for optional equipment*	kg	255	233	190
Technically permissible maximum laden mass*	kg	3499	3499	3499
Permitted number of seats (including driver)*		4	4	4 - 5 0
Refrigerator volume (thereof freezer), approx.	I	137 (15)	137 (15)	137 (15)
Waste water tank, approx.	1	90	90	90
Fresh water tank capacity, total/ Fresh water tank capacity at driving	g I	116 / 20	116 / 20	116 / 20
Measurement storage opening left (W x H)	cm	40 x 75 O / 40 x 110	85 x 65 O / 85 x 110	85 x 110
Measurement storage opening right (W x H)	cm	75 x 75 O / 75 x 110	85 x 65 O / 85 x 110	85 x 110



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to  $\pm$  5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

### Trend I A Class Technical info







Trend I A Class		I 7057 EB	I 7057 DBL	I 7057 EBL
Standard chassis		Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform	Fiat Ducato Light Low Platform
Emission standards		Euro 6e	Euro 6e	Euro 6e
Overall length, approx.	cm	740	740	740
Overall width, approx.	cm	233	233	233
Overall height, approx.	cm	300 1)	300 1)	300 1)
Headroom in living area, approx.	cm	205	205	205
Towable load braked/unbraked	kg	2000 / 750	2000 / 750	2000 / 750
Wheelbase, approx.	mm	4035	4035	4035
Bed dimension: Front bed, L x W, approx.	cm	196 x 150	196 x 150	196 x 150
Bed dimension: Central / middle bed, L X W, approx.	cm	210 x 118 - 80 O		
Bed dimension: Rear bed, L x W, approx.	cm	214 x 80 / 212 x 80 / 211 x 201	195 x 150	211 x 80 / 207 x 80 / 211 x 198
Sleeping berths standard / max.		4/50	4	4
Standard engine		140 MultiJet 3	140 MultiJet 3	140 MultiJet 3
kW (bhp)		103 (140)	103 (140)	103 (140)
Mass in running order (+/-5%)*	kg	3061 (2908 to 3214)*	3055 (2902 to 3208)*	3043 (2891 to 3195)*
Manufacturer-specified mass for optional equipment*	kg	99	105	117
Technically permissible maximum laden mass*	kg	3499	3499	3499
Permitted number of seats (including driver)*		4 - 5 0	4	4
Refrigerator volume (thereof freezer), approx.	I	137 (15) / 137 (15) 🔿	137 (15) / 137 (15) 〇	137 (15) / 137 (15) 🔾
Waste water tank, approx.	- 1	90	90	90
Fresh water tank capacity, total/ Fresh water tank capacity at drivin filling	ig I	116 / 20	116 / 20	116 / 20
Measurement storage opening left (W x H)	cm	90 x 75 O / 90 x 110	90 x 110	90 x 75 O / 90 x 110
Measurement storage opening right (W x H)	cm	90 x 75 O / 90 x 110	90 x 110	90 x 75 🔾 / 90 x 110

O Optional equipment ─ Not possible ● Standard equipment ◆ Mandatory △ Not known at the time of publication



The specified mass in running order is a default value defined in the type-approval procedure. Due to manufacturing tolerances, the actual weighed mass in running order may deviate from the value stated above. Deviations of up to  $\pm$  5 % of the mass in running order are legally permissible and possible. The permissible range in kilograms is given in brackets after the mass in running order. The manufacturer-specified mass for optional equipment is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. The limitation of optional equipment is intended to ensure that the minimum pay-mass, i.e. the legally prescribed free mass for baggage and retrofitted accessories, is actually available for the vehicle load capacity of the vehicles delivered by Dethleffs. The real weight of your vehicle ex works can only be determined when it is

weighed at the end of the line. If, in exceptional cases, the weighing shows that the actual load capacity falls below theminimum pay-mass despite limiting the optional equipment due to a permissible weight deviation, we will check together with your trade partner and you whether we should, for example, increase the load capacity of the vehicle, reduce the number of seats or remove optional equipment before delivering the vehicle. The technically permissible maximum laden mass of the vehicle and the technically permissible maximum mass on the axle must not be exceeded. Detailed information & explanations on the subject of weight and the configuration of the vehicle can be found in the section Legal information. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

Flat Chassis   Flat Chars	1 6617 EB 1 6817 EB 1 6877 1 7057 EB 1 7057 EB
Fish Durace Light Now platform (3,499 kg), Multipet 140 (2.2 l / 103 kw / 140 hg), 6-speed manual transmission	
File Chassis Tectures  File Chassis Tectures  File Chassis Tectures  File Chassis Tectures  Altichetic device  Automatic Brake Assist after a collision Capitain seats: integrated headinsts, two ammests, swived function Chassis in right-hand drive version Capitain seats: integrated headinsts, two ammests, swived function Chassis in right-hand drive version Crosswind Assist Cruse control  Use holder in the centre of the darbboard Darabboard with alturnium application Dicsel tank 90 litre (and, 194 Addius tank Driver and passenger ariangs Driver and passenger ariangs Driver and passenger ariangs Driver and passenger ariangs Driver and passenger detection Driver's Charles Driver, 194 Act File Truntium (and 194 Addius tank Driver and passenger detection Driver's Charles Driver, 194 Act File Mark Assist, Traction Plus, Hill Holder and Hill Descent Control  Florit-whole drive Give Injury and this adjustable incl. two padded ammests for the driver and front passenger seat Leather steering wheel and gear know withleather sleeve Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Leather steering wined and gear know withleather sleeve Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Leather steering wined and gear know withleather sleeve Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Leather steering wined and gear know withleather sleeve Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Leather steering wined and gear know withleather sleeve Low withration coach-style exterior minions that can be heated and adjusted electrically (two-piece) Leather steering wined with control elements Leather steering wined with exhaust on the left side  Sleering wined with control elements Leather steering wined wined wined wined the	
ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)  ABS (anti-lock braking system) / EBD (electronic brakeforce distribution)  Auti-the Hid drove  Automatic Brake Assist after a collision  Captain seats: integrated headrests, two armrests, swivel function  Captain seats: integrated headrests, two armrests, swivel function  Coptain seats: integrated headrests, two armrests, swivel function  Coptain seats: integrated headrests, two armrests, swivel function  Crosswell Assist  Crosswell Assi	hp), 6-speed manual transmission
ABS (anti-lock braking system) / IBD (electronic brakeforce distribution) Anti-thefic device Anti-thefic device Anti-thefic device Anti-thefic device Anti-thefic device Captain seals: integrated headrests, two armiests, swivel function Captain seals: integrated headrests, two armiests, swivel function Chassis in right-hand drive version Crosswind Assist Cruise control Consswind Assist Cruise Control Con	
Automatic Brake Assist after a collision Captain seats integrated headrests, two armrests, swivel function Chassis in right-hand drive version Copia for the integrated headrests, two armrests, swivel function Chassis in right-hand drive version Cup holder in the centre of the doshboard Cup holder and passenger alrabage Chiver and passenger alrabage Chiver and passenger defection Chiver's cap manual A/C Size in Assist Incine Plus, Hill holder and Hill Descent Control Front-wheel drive CRP lightweight lead signified the centre of the driver and front passenger seat Leather steering wheel and gate knob withlesather sleeve Cup what and distribution coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinds in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the centre of the	
Automatic Brake Assist after a collision Captain seats integrated headrests, two armrests, swivel function Chassis in right-hand drive version Copia for the integrated headrests, two armrests, swivel function Chassis in right-hand drive version Cup holder in the centre of the doshboard Cup holder and passenger alrabage Chiver and passenger alrabage Chiver and passenger defection Chiver's cap manual A/C Size in Assist Incine Plus, Hill holder and Hill Descent Control Front-wheel drive CRP lightweight lead signified the centre of the driver and front passenger seat Leather steering wheel and gate knob withlesather sleeve Cup what and distribution coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinds in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the windscreen and side windows of the drivers cab for the best insulation and privacy CRIGHT-hand drive with exhaust on the left side Size in the centre of the	
Automatic Brake Assist after a collision Capitain seats: integrated headnests, two armests, swivel function Capitain seats: integrated headnests, two armests, swivel function Crosswind Assist Cruise control Cup holder in the centre of the dashboard Dashboard with aluminium application Dashboard with aluminium application Diesel tank 90 life incl. 194 Additus tank Driver and passenger aithags Driver and passenger aithags Driver and passenger aithags Driver and passenger detection Drivers can branal A/C ESP incl. ASP, Traction Plus, Hill Holder and Hill Descent Control Front-wheel drive Gire lightweight leaf spring Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat Leather steering wheel and gear knob withleather sleeve Low withartion coden style exterior mirrors that can be heated and adjusted electrically (two piece) Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer stability Assist Travier stability Assist Travier stability Assist Vinter tyres Art's Camping (with snowflake)  Exterior Ceatures  Dethiciffs Exclusive rear light carrier with ShapeLine LLD taillights, 3rd brake light integrated in rear spoiler and retracted rear wall To crn wide habitation door Reference of Care light mounting with black diffuser, extended slickers, skidplate "red") Financial for a light mounting with black diffuser, extended slickers, skidplate "red") Financial rear sake White tyres Art's Camping with black diffuser, extended slickers, skidplate "red") Financial rear sake with conflortable, wide, electric step Habitation door Gire a light contrable, wide, electric step Habitation access with conflortable, wide, electric step Habitation access with conflortable, wide, electric step Habitation or any gained and flathes with one hand operation, rear lowering (50 kg surface load), heated, with lashing rails, Randon and some gained and flathes with o	
Chassis in right-hand drive version Crosswind Assist Cruse control Cup holder in the centre of the dashboard Dashboard with aluminium application Disesel tank 90 lite incl. 194. AdBlust tank Oriver and passenger elabags Driver and passenger elabags Driver and passenger elabetion Drivers cab manual A/C Espi incl. ASE, Traction Pilus, Hill Holder and Hill Descent Control Front-wheel drive GRP lightweight leaf spring Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat Leather Steering wheel and gear knob withleather sleeve Low-wibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleatable Blinds in the windscreen and side windows of the driver's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer Subblity Assist Trye inflation kit and towing eye Widened rear axie  Widened rear	
Chassis in right-hand drive version Crosswind Assist Cruse control Cup holder in the centre of the dashboard Dashboard with aluminium application Disesel tank 90 lite incl. 194. AdBlust tank Oriver and passenger elabags Driver and passenger elabags Driver and passenger elabetion Drivers cab manual A/C Espi incl. ASE, Traction Pilus, Hill Holder and Hill Descent Control Front-wheel drive GRP lightweight leaf spring Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat Leather Steering wheel and gear knob withleather sleeve Low-wibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleatable Blinds in the windscreen and side windows of the driver's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer Subblity Assist Trye inflation kit and towing eye Widened rear axie  Widened rear	
Crosswind Assist Cruise control  Deshboard with aluminium application Discelt tank 90 litric inthe centre of the dashboard Deshboard with aluminium application Discelt tank 90 litric ind. 191. Addition tank Driver and passenger airbags Driver and passenger detection Driver's cab manual A/C ESP ind. ASIS, Traction Plus, Hill Holder and Hill Descent Control Front-wheel drive GSP lightweight leaf spring Height and till adjustable ind. two padded armrests for the driver and front passenger seat Leather steering wheel and gear knob withbeather sleeve Low-withartion coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinds in the windscreen and side windows of the driver scab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer Stability Assist Trai	
Cup holder in the centre of the dashboard Dashboard with aluminium application Disest lank 90 II front. 1914 Addluct ank Driver and passenger airbags Driver and passenger airbags Driver and passenger detection Driver's can braunal A/C ESP Incl. ASR, Traction Plus, Hill Holder and Hill Descent Control Front-wheel drive GEP lightweight leaf spring Height and tilt adjustable incl. two padded armests for the driver and front passenger seat Leasther steering wheel and gear knob withleather sleeve Low whollon condst-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer Stability Assist Winter tyres M-S Camping (with snowflake) Exterior Gebrues Winter tyres M-S Camping (with snowflake) Exterior desting and left Double glazed flush-fitting windows with blackout 6 mosquito protection Driver's cab door left PSP insulation Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red") Floor thickness. 49 mm, side wall thickness; 34mm and roof thickness. 35 mm Flyscreen habitation door GRP roof Habitation access with comfortable, wide, electric step	
Dashboard with aluminium application Diesel tank 90 litre ind. 191 Additue tank Driver and passenger airbags Driver and passenger detection Driver's cab manual A/C SEP ind. ASR, Traction Plus, Hill Holder and Hill Descent Control Front-wheel drive GRP lightweight leaf spring GRP lightweight leaf spring Leather steering wheel and gear knob withleather sleeve Low-bibation coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinds in the windscreen and side windows of the driver's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Sleering wheel with control elements Trailer Stability Assist Trailer Stability Assist Winter tyres MrS Camping (with snowlfake) Exterior features Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door Bedroom window right and left Double-glazed flush-fitting windows with blackout & mosquito protection Driver's cab door left ESP insulation Exterior features Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door Bedroom window right and left Double-glazed flush-fitting windows with blackout & mosquito protection Driver's cab door left ESP insulation Exterior features Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall On the change of the strength of the change	
Direct and passenger airbags Driver and passenger detection Drivers cab manual A/C ESP incl. ASR. Traction Pics, Hill Holder and Hill Descent Control Front-wheel drive GRP lightweight leaf spring Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat Leather steering wheel and gear knob withleather sleeve driver and front passenger seat Leather steering wheel and gear knob withleather sleeve driver and front passenger seat Leather steering wheel and gear knob withleather sleeve driver and front passenger seat Leather steering wheel and gear knob withleather sleeve drivers cab for the best insulation and privacy Hight-hand drive with exhaust on the left side Steering wheel with control elements Trailer Stability Assist Widened rear axle Winter tyres Mr-S Camping (with snowflake)  Patterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall To cm wide habitation door Bedroom window right and left Double-glazed flush-fitting windows with blackout 8 mosquito protection Driver's cab door left PSP insulation Even iso-Protect comfort floor in the living area without landings Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red") Floor thickness: 49 mm, side wall thickness: 34 mm and roof thickness: 35 mm Flyscreen habitation door with window incl. blackout and central locking (incl. cab door) Lifetime Smart construction technology: ort free floor construction with no wood inserts, with GRP cladding on the underslung and toof RP roof Ranoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	0 0 0 0 0
Driver and passenger airbags Driver and passenger detection Driver's cab manual A/C  ESP Incl. ASR, Traction Plus, Hill Holder and Hill Descent Control Front-wheel drive GER lightweight leaf spring Height and till adjustable incl. two padded armrests for the driver and front passenger seat Leather steering wheel and gear knob withleather sleeve Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece) Pleated blinids in the windscreen and side windows of the driver's cab for the best insulation and privacy Right-hand drive with exhaust on the left side Steering wheel with control elements Trailer Stability Assist Tyre inflation kit and towing eye Widened rear axle Widened rear axle Widened rear axle Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door Bedroom window right and left Double-glazed flush-fitting windows with blackout & mosquito protection Driver's cab door left PSP insulation P	
Driver's cab manual A/C  SEP inct. ASR, Traction Plus, Hill Holder and Hill Descent Control  Front-wheel drive  GRP lightweight leaf spring  Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat  Leather steering wheel and gear knob withleather sleeve  Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Trailer Stability Assist  Trailer Stability Assist  Winder of rear axle  Winter tyres M-S Camping (with snowflake)  Exterior features  Exterior features  Dethielfs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  O	
Driver's cab manual A/C  ESP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control  Front-wheel drive  GRP lightweight leaf spring  Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat  Leather steering wheel and gear knob withleather sleeve  Leather steering wheel and gear knob withleather sleeve  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winder drear axle  Winder yres M-'s Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  PSP insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable, electric step  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 175x105 cm in the lounge  Rear garage: two garage door/haches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
ESP incl. ASR, Traction Plus, Hill Holder and Hill Descent Control  Front-wheel drive  Ropr lightweight leaf spring  Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat  Leather steering wheel and gear knob withleather sleeve  Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cah door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior feaging off (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable coupe entrance  Habitation access with comfortable, electric step  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Rap roor access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Rap roor access with comfortable coupe	
Front-wheel drive  GRP light weight leaf spring  GRP light weight leaf spring  Leather steering wheel and gear knob withleather sleeve  Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre Inflation kit and towing eye  Windened rear axle  Winter tyres M-S Camping (with snowllake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  PPS insulation  Exterior design of (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation over with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Rep lightweight leaf spring  Height and tilt adjustable inct, two padded armrests for the driver and front passenger seat  Leather steering wheel and gear knob withleather sleeve  OPRICE Steering wheel and gear knob withleather sleeve  OPRICE Steering wheel strein mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  To cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34 mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 10x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 10x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 10x40 cm with lashing rails.	
Height and tilt adjustable incl. two padded armrests for the driver and front passenger seat  Leather steering wheel and gear knob withleather sleeve  Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Trailer Stability Assist  You inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  Eyes insulation  Eyen iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Leather steering wheel and gear knob withleather sleeve  Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tryle Inflation kit and towing eye  Widened rear axle  Widened rear axle  Widened rear axle  Wither tyres M+5 Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Low-vibration coach-style exterior mirrors that can be heated and adjusted electrically (two-piece)  Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Widened rear axle  Witner tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Divier's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	passenger seat • • • • • •
Pleated blinds in the windscreen and side windows of the drive's cab for the best insulation and privacy  Right-hand drive with exhaust on the left side  Steering wheel with control elements  Tryie inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable coupe entrance  Habitation access with comfortable wide, electric step  Habitation access with comfortable, wide, electric step  Habitation access with comfortable coupe entrance  Habitation access with comfortable wide, electric step  Ranoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Right-hand drive with exhaust on the left side  Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winter tyres M+5 Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  Eyes Insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation foor with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with lashing rails,	
Steering wheel with control elements  Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Widened rear axle  Widened rear axle  Dethelfis Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation access with comfortable, wide, electric step  Habitation access with comfortable, wide, electric step  Habitation scess with comf	e best insulation and privacy
Trailer Stability Assist  Tyre inflation kit and towing eye  Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  RBP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 40x40 cm with endown hee-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Widened rear axle  Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with Shapetine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  RB Proof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Winter tyres M+S Camping (with snowflake)  Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall 70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Exterior features  Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout 8 mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Dethleffs Exclusive rear light carrier with ShapeLine LED taillights, 3rd brake light integrated in rear spoiler and retracted rear wall  70 cm wide habitation door  8edroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
70 cm wide habitation door  Bedroom window right and left  Double-glazed flush-fitting windows with blackout 8 mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Bedroom window right and left  Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	light integrated in rear spoiler and retracted rear wall $lacktriangle$ $lacktriangle$ $lacktriangle$ $lacktriangle$
Double-glazed flush-fitting windows with blackout & mosquito protection  Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	0 0 0 0 0
Driver's cab door left  EPS insulation  Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Even Iso-Protect comfort floor in the living area without landings  Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Exterior design GT (rear light moulding with black diffuser, extended stickers, skidplate "red")  Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Floor thickness: 49 mm, side wall thickness: 34mm and roof thickness: 35 mm  Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Flyscreen habitation door  GRP roof  Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Habitation access with comfortable coupe entrance Habitation access with comfortable, wide, electric step Habitation door with window incl. blackout and central locking (incl. cab door) Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed Panoramic skylight 75x105 cm in the lounge Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Habitation access with comfortable coupe entrance  Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	• • • • •
Habitation access with comfortable, wide, electric step  Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Habitation door with window incl. blackout and central locking (incl. cab door)  Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	• • • • •
Lifetime Smart construction technology: rot-free floor construction with no wood inserts, with GRP cladding on the underslung and roof  Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
roof Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed Panoramic skylight 75x105 cm in the lounge Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
Panoramic skylight 40x40 cm with flyscreen and blackout blinds above the pull-down bed  Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	wood inserts, with GRP cladding on the underslung and
Panoramic skylight 75x105 cm in the lounge  Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	pull-down bed
Rear garage: two garage door/hatches with one-hand operation, rear lowering (150 kg surface load), heated, with lashing rails,	
	ring (150 kg surface load), heated with lashing rails
	ang (155 mg solitote 1868), mestes, min toshing rolls,
Side panels and rear panel made of resistant high-gloss GRP with smooth, shiny surface	hiny surface

Standard equipment	I 6617 EB	I 6817 EB	1 6877	I 7057 EB	1 7057 DBL	I 7057 EBL
Exterior body painted in white	•	•	•	•	•	•
Interior design						
Upholstery Saros			•	•	•	•
Wood décor Ashton	•	•	•	•	•	•
Textile equipment						
Rear beds with ergonomic wooden slatted frames and 150 mm thick 7-zone premium mattresses made of climate-regulating material	•	•	•	•	•	•
Furniture layouts						
AirPlus overhead locker rear ventilation to avoid condensation	•	•	•	•	•	•
Comfortable lounge seating group with 2 folding seats incl. 3-point belts incl. Isofix and free-standing, rigid table base	_	_	_	_		•
Cosy L-shaped seating group with free-standing, lowerable table base and 2 integrated 3-point belts	•	•	•	•	-	_
Double bed high in the rear, transverse	_	_		_	_	_
Floor-to-ceiling closet with pull-out step for convenient access to the bed	_	_	•	_	_	_
Floor-to-ceiling wooden sliding door to the bedroom	-	_	_			
Height-adjustable double bed	Ξ	_	_	_	•	_
High-level single beds incl. comfortable access via steps			_		-	
Manual pull-down bed in the driver's cab		•	•	•	•	•
Modern entrance shelf with practical storage compartments and tension straps	_					
Multifunctional storage space underneath the double bed incl. wardrobe, accessible from inside and outside, illuminated, bed frame adjustable	_	_	•	_	_	_
Option to convert single bed to double bed			_		_	
Overhead locker doors with soft-close function		•		•		
Overhead lockers in the rear area						
Two practical tension nets under the overhead locker in the rear bed  Two practical tension nets under the overhead locker in the rear bed						
Wardrobe to the left and right of the queen-size bed						
Kitchen					Ť	
Fridge (137 l)						
Gourmet kitchen: two-ring hob, large drawers, cutlery tray, bin and generous worktop  Kitchen backsplash with spice rule						
MultiFlex rail system incl. hooks (further accessories via Dethleffs Original Accessories)						
Oven in the kitchen floor units	_	•	•	•	_	_
Oven in the kitchen floor units  Bathroom	•	_	-	-	•	•
Equipped with cabinets, storage compartments, large mirrors, toothbrush mug and toilet paper holder						
Large bathroom with separate shower and toilet with locking door to the lounge						
Shower grate						
Swiveling bathroom wall for optimal use of space	•	_	_	_	_	_
Multimedia						
DAB+ radio antenna mounted on the roof		_	_			_
Flat-screen TV bracket						
Pre-wiring for first rear view camera						
Pre-wiring for satellite system		•	•	•		•
Preparation for radio system incl. sound package in the driver's cabin		•		•	•	•
Heating						
Gas hot air heating 6kW with 1.8kW electric heating element and hot water boiler incl. digital control panel						
Heating in the seating unit for optimum heat distribution, built-in						
Air Conditioning						
Pre-wiring for roof A/C	•	•	•	•	•	•
Electrical installation						
Automatic switch-on/disconnect for starter battery, leisure battery and refrigerator				•	•	•
Awning light 12 V						

Standard equipment	1 6617 EB	I 6817 EB	1 6877	I 7057 EB	I 7057 DBL	I 7057 EBL
Electric block with integrated overvoltage protection and separate ground fault circuit breaker	•	•	•		•	
Functional lighting (surface-mounted and recessed spotlights)			•	•	•	
LED lighting throughout the vehicle						
Leisure battery AGM, 95 Ah			•			
Light Moments: Clad seat chest side with indirect lighting					_	_
Light Moments: Entrance segment with indirect lighting	_					
Light Moments: Indirect ambient lighting above the overhead lockers	•		•			
Light Moments: Indirect lighting in the bathroom with illuminated shower panel	_					
Light Moments: Indirect wall surface ambient lighting						
Light Moments: illuminated kitchen splashback						
Number of sockets 1x 12V, 7x 230V, 4x USB	•		•			
On-board control panel						
Pre-wiring for solar	•		•			
Spotlights in the roof lining above the habitation door						
Water supply						
Fresh water tank in insulated and heated area	•		•	•	•	•
Insulated waste water tank			•		•	
Submersible pump	•				•	
Gas supply						
Storage space for 2 gas bottles with a filling weight of 11 kg each, with simplified access	•	•	•	•	•	•
Safety						
Smoke detector	•	•	•	•	•	•

### PACKAGES TREND I A CLASS

Package	Package X (awning 4.0m) (13734)	х	х	Package One (awning 4.0m) (13732)	One	Package One (awning 5.0m) (13732)	Two	Two	Two
Integrated single-lens rear view camera	х	Х	х	Х	Х	Х	Х	Х	Х
Omnistor cassette awning 4.0 m (manual)	х			х			х		
Omnistor cassette awning 4.5 m (manual)		х			х			х	
Omnistor cassette awning 5.0 m (manual)			х			х			х
Flat-screen TV bracket				х	х	х	х	х	х
Automatic HD satellite system 65 Twin				х	х	Х	х	Х	х
Flat screen 22" HD TV				х	х	х			
Flat screen 32" HD TV							х	Х	Х
Additional weight (kg)*	35	39	41	51.5	55.5	57.5	54.5	58.5	60.5

Package	Winter Comfort Package ALDE (13736)	Winter Comfort Package ALDE (13736)	Winter Comfort Package ALDE (13736)
Switch for water pump	Х	Х	X
Insulated under-floor pipes	Х	Х	X
Insulated waste water tank	х	х	x
Waste water tank and pipes electrically heated	Х	Х	x
Hot-water carpet for the driver's cab	Х	Х	x
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	Х	х	
XPS insulation	Х		
XPS insulation		Х	
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel			х
XPS insulation			Х
Additional weight (kg)*	66.7	68.7	75.7



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Package	Winter Comfort Package hot air heating (13735)	Winter Comfort Package hot air heating (13735)	Winter Comfort Package hot air heating (13735)
Switch for water pump	Х	Х	Х
Insulated under-floor pipes	Х	Х	Х
Insulated waste water tank	Х	х	Х
Waste water tank and pipes electrically heated	Х	х	Х
Gas hot air heating 6kW with 1.8kW electric heating element and hot water boiler incl. digital control panel	Х	х	Х
XPS insulation	Х		
XPS insulation		Х	
XPS insulation			Х
Additional weight (kg)*	24.2	26.2	27.2

#### Chassis Package (14582)

Automatic cab air conditioning, digital speedometer with 7" instrument cluster and wireless phone charger in the centre console Electric parking brake

LED daytime running lights

Additional weight (kg)\* -8.1

△ Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for

optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and explanations on the subject of weight can be found in the Legal information section.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 6617 EB	I 6817 EB	1 6877	I 7057 EB	1 7057 DBL	1 7057 EBL
Fiat chassis									
Fiat Ducato Light low platform (3,499 kg), MultiJet 140 (2.2 l / 103 kW / 140 hp), 8-speed torque converter automatic transmission	_	60	140A	0	0	0	0	0	0
Fiat Ducato Light low platform (3,499 kg), MultiJet 180 (2.2 l / 132 kW / 180 hp), 8-speed torque converter automatic transmission	_	60	180A	0	0	0	0	0	0
Fiat Ducato Maxi low platform (4,250 kg), MultiJet 180 (2.2 l / 132 kW / 180 hp), 8-speed torque converter automatic transmission	_	60	M180A	0	0	0	0	0	0
Weight upgrade									
Weight upgrade 3,650 kg	_	0	10769	0	0	0	0	0	0
Fiat chassis features									
Additional seat <sup>8)</sup>	_	14.5	435	_	_	0	0	_	_
Rear corner steadies (2 pieces)	_	6	390	0	0	0	0	0	0
Reinforced spring for front axle	_	3.75	1889	0	0	0	0	0	0
Tow bar (check permissible gross towing weight for trailer operation)	_	62	273	0	_	_	_	_	_
Tow bar (check permissible gross towing weight for trailer operation)	_	65	273	_	0	0	_	_	_
Tow bar (check permissible gross towing weight for trailer operation)	_	66	273	_	_	_	0	0	0
Exterior features									
Bike rack for 3 bikes (lowerable)	_	20.7	7482	0	0	0	0	0	0
Bike rack for 3 bikes (rear)	_	10.5	938	0	0	0	0	0	0
Double floor in rear garage	_	10	1890	0	_	_	_	_	_
Double floor in rear garage	_	12	1890	_	_	_	0	0	0
Double floor in rear garage	_	13	1890	_	0	0	_	_	_
Roof vent with fan	_	1.5	7507	0	0	0	0	0	0
Interior design									
Upholstery Heron (partial textile-leather)	_	0	13726	0	0	0	0	0	0
Upholstery Yoko	_	0	13725	0	0	0	0	0	0
Textile equipment									
Carpet, loose	_	5.7	851	0	_	_	-	_	
Carpet, loose	_	6.2	851	_	0	_	=	_	_
Carpet, loose	_	5.5	851	_	_	0	_	_	_
Carpet, loose	_	7.1	851	_	_	_	0	_	_
Carpet, loose	_	8.5	851	_	_	_	_	0	_
Carpet, loose		7.5	851	_	_	_	_	_	0
Furniture layouts									
Bed convert for seating lounge transverse	_	5.5	1944	_	_	0	_	_	_
Bed convert for seating lounge transverse	_	8	1944	_	_	_	0	_	_
ISOFIX child seat bracket for third and fourth seat facing direction of travel	_	4	8125	0	0	0	0	_	_
Low single-beds for comfortable access and high headroom	_	-13	510	0	0	_	_	_	_
Low single-beds for comfortable access and high headroom		-10.5	510	_	_	_	0	_	0
Bathroom									
Window in bathroom	_	5	372	-	0	0	0	0	0
Multimedia									



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for actional equipment change in the model programs. This is a calculated to the control of the selected optional equipment change in the model programs. This is a calculated to the control of the selected optional equipment in the model programs. optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes. footnotes.

Optional equipment*	Included in package	Additional weight (kg)*	Code	I 6617 EB	I 6817 EB	1 6877	I 7057 EB	17057 DBL	17057 EBL
Dethleffs Naviceiver incl. DAB+, truck navigation, wireless Apple CarPlay and Android Auto <sup>5)</sup>	_	3.65	9582	0	0	0	0	0	0
Second rear view camera in rear moulding	_	1	11541	0	0	0	0	0	0
Heating									
Floor heating electric (partial) <sup>13)</sup>	_	5	763	0	0	0	0	0	0
Hot-water carpet for the driver's cab <sup>12)</sup>	_	3.5	6709	0	0	0	0	0	0
Hot-water floor heating 12)	_	11	1603	0	0	0	0	0	0
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	_	40	761	0	0	0	_	_	_
Hot-water heating with boiler, automatic drain valve and shut-off valve for the sleeping area and digital control panel	_	46	761	_	_	_	0	0	0
Electrical installation									
2nd Leisure battery Dual Battery System (Lithium), 140 Ah <sup>6)</sup>	_	19	13968	0	0	0	0	0	0
Second leisure battery AGM, 95 Ah <sup>6)</sup>	_	27	830	0	0	0	0	0	0
Solar power system 100 watt	_	12.6	922	0	0	0	0	0	0
Water supply									
Outdoor shower (cold water)	_	0.5	793	0	0	0	0	0	0
Switch for water pump	_	0.2	397	0	0	0	0	0	0
Gas supply									
Automatic gas cylinder switchover incl. crash sensor, EisEx and gas filter	_	2.5	1577	0	0	0	0	0	0
Outdoor gas socket gas pressure 30 mbar	_	1.3	878	0	0	0	0	0	0
Safety									
2 kg fire extinguisher	_	4	1878	0	0	0	0	0	0
Safe	_	4.7	13739	0	0	0	0	0	0
Packages									
Chassis Package	_	-8.1	14582	0	0	0	0	0	0
Package One (awning 4.0m)	_	51.5	13732	0	_	_	_	_	_
Package One (awning 4.5m)	_	55.5	13732	_	0	0	_	_	_
Package One (awning 5.0m)	_	57.5	13732	_	_	_	0	0	0
Package Two (awning 4.0m)	_	54.5	13733	0	_	_	_	_	_
Package Two (awning 4.5m)	_	58.5	13733	_	0	0	_	_	_
Package Two (awning 5.0m)	_	60.5	13733	_	_	_	0	0	0
Package X (awning 4.0m)	_	35	13734	0	_	_	_	_	_
Package X (awning 4.5m)	_	39	13734	_	0	0	_	_	_
Package X (awning 5.0m)	_	41	13734	_	_	_	0	0	0
Winter Comfort Package ALDE Winter Comfort Package ALDE	_	66.7 68.7	13736 13736	0					
Winter Comfort Package ALDE  Winter Comfort Package ALDE	_	75.7	13736	_			0	0	0
Winter Comfort Package Not air heating	_	24.2	13735	0	_	_	_	_	_
Winter Comfort Package hot air heating	_	26.2	13735	_	0	0	_	_	
Winter Comfort Package hot air heating	_	27.2	13735	_	_	_	0	0	0
Miscellaneous									
Registration documents (CoC papers)	-	0	15152	+	+	<b>*</b>	<b>*</b>	<b>*</b>	+

O Optional equipment — Not possible Standard equipment lack Mandatory  $\Delta$  Not known at the time of publication



The factory installation of optional equipment increases the actual mass of the vehicle and reduces the pay-mass. The additional weight indicated for packages and optional equipment shows the additional weight compared to the standard equipment of the respective model or layout. The total weight of the selected optional equipment must not exceed the manufacturer-specified mass for optional equipment shown in the model overviews. This is a calculated value for each type and layout that Dethleffs uses to determine the maximum weight available for factory-fitted optional equipment. Detailed information and

explanations on the subject of weight can be found in the Legal information section. An increase of load capacity increases the manufacturer-specified mass for optional equipment. The increase results from the higher pay-mass due to the alternative chassis. The increased tare weight of the alternative chassis and, in particular, the weight for any mandatory heavier engine variants (e.g. 180 hp) must be deducted from this. For a more detailed description of all mandatory technical dependencies, please refer to the explanations on the footnotes.

#### IMPORTANT INFORMATION REGARDING THE SELECTION OF YOUR MOTORHOME

The weight specifications and tests for **motorhomes** are uniformly regulated throughout the EU in EU Implementing Regulation No. 2021/535 (until June 2022: EU Implementing Regulation No. 1230/2012). We have summarised and explained the key terms and legal requirements from this **regulation** for you below. Our **dealers** and the Dethleffs configurator on our website offer you additional assistance in configuring your vehicle.

1. Technically permissible maximum laden mass

The technically permissible maximum laden mass of the vehicle (e.g. 3,500 kg) is a mass specification set by the manufacturer which the vehicle must not exceed. Information on the technically permissible maximum laden mass of the model you have chosen can be found in the technical data. If the vehicle exceeds the technically permissible maximum laden mass in everyday driving, this constitutes an administrative offence which may result in a fine.

#### 2. Mass in running order

In simple terms, the mass in running order is the basic vehicle with standard equipment plus a legally fixed standard weight of 75 kg for the driver. This essentially includes the following items:

- the unladen weight of the vehicle together with the bodywork, including operating fluids such as greases, oils and coolants;
- the standard equipment, i.e. all equipment items that are included as standard in the factory-fitted scope of delivery;
- the fresh water tank filled to 100 % in driving mode (driving fill according to manufacturer's specifications;) and an aluminium gas cylinder filled to
- the fuel tank, which is 90 % full, including fuel;
- the driver, whose weight regardless of the actual weight is generally specified as 75 kg in accordance with EU law.

Information on the **mass in running order** can be found for each model in our sales documents. It is important to note that the value for **mass in running order** given in the sales documents is a default value determined in the **type-approval procedure** and verified by the authorities. It is legally permissible and possible for the **mass in running order** of the vehicle delivered to you to deviate from the nominal value stated in the sales documents. The legally permissible **tolerance** is ± 5 %. In this way, the EU legislator accounts for the fact that certain fluctuations in the **mass in running order** occur due to variations in the weight of supplied parts as well as due to processes and weather conditions.

These weight deviations can be illustrated by means of an example calculation:

- Mass in running order acc. to sales documents: 2,850 kg
- Legally permissible tolerance of ± 5 %: 142.50 kg
- Legally permissible range of **mass in running order**: 2,707.50 kg to 2,992.50 kg

The specific range of permissible weight deviations can be found for each model in the technical data. Dethleffs makes great efforts to reduce weight variations to the minimum that is unavoidable for production reasons. **Deviations** at the upper and lower end of the range are therefore very rare; however, they cannot be completely ruled out technically, even

with all optimisations. The real weight of the vehicle and compliance with the permissible **tolerance** is therefore checked by Dethleffs by weighing each vehicle at the **end of the line**.

#### 3. Mass of the passengers

The **mass of the passengers** is set a standard value of 75 kg for each seat provided by the manufacturer, regardless of the actual weight of the passengers. The **mass of the driver** is already included in the **mass in running order** (see no. 2 above) and is therefore not included again. In the case of a **motorhome** with four **permitted seats**, the **mass of the passengers** is therefore 3  $^*$  75 kg = 225 kg.

#### 4. Optional equipment and actual mass of the vehicle

**Optional equipment** (also: additional equipment) includes, according to the legal definition, all optional equipment parts not included in the **standard equipment** which are fitted to the vehicle under the responsibility of the manufacturer – i.e. ex works – and can be ordered by the customer (e.g. awning, bicycle or motorbike carrier, satellite system, solar system, oven, etc.). Information on the individual or package weights of the **optional equipment** that can be ordered can be found in our sales documents. **Optional equipment** in this sense does not include other accessories that are retrofitted by the **dealer** or you personally after the vehicle has been delivered ex works.

The mass of the vehicle in running order (see no. 2 above) and the mass of the optional equipment fitted to a specific vehicle at the factory are together referred to as the actual mass. You will find the corresponding information for your vehicle after handover under item 13.2 of the Certificate of Conformity (CoC). Please note that this specification also represents a standardised value. Since the mass in running order – as an element of the actual mass – is subject to a legally permissible tolerance of ± 5 % (see no. 2), the actual mass may also deviate accordingly from the stated nominal value.

#### 5. Pay-mass and minimum pay-mass

The installation of optional equipment is also subject to technical and legal limits: Only so much optional equipment can be ordered and fitted at the factory that sufficient free weight remains for baggage and other accessories ("pay-mass") without exceeding the technically permissible maximum laden mass. The pay-mass is calculated by subtracting the mass in running order (nominal value according to sales documents, see no. 2 above), mass of the optional equipment and the mass of the passengers (see no. 3 above) from the technically permissible maximum laden mass (see no. 1 above). The EU regulations stipulate a fixed minimum pay-mass for motorhomes, which must remain as a minimum for baggage or other non-factory-fitted accessories. This minimum pay-mass is calculated as follows:

Minimum pay-mass in kg ≥ 10 \* (n + L)

Where: "n" is the maximum number of passengers plus the driver and "L" is the overall length of the vehicle in metres.

For a motorhome with a length of 6 m and 4 approved seats, the minimum pay-mass is therefore e.g. 10 kg  $^*$  (4 + 6) = 100 kg.

To ensure that the minimum pay-mass is maintained, there is a maximum combination of optional equipment that can be ordered for each vehicle model. In the above example with a minimum pay-mass of 100 kg, the total mass of optional equipment for a vehicle with four permitted seats and a mass in running order of 2,850 kg should not exceed 325 kg:

3,500 kg technically permissible maximum laden mass

- 2,850 kg mass in running order
 - 3\*75 kg mass of the passengers
 - 100 kg minimum pay-mass

325 kg maximum permissible mass of optional equipment

It is important to note that this calculation is based on the default value for mass in running order as defined in the type-approval procedure, without taking into account the permissible weight deviations for mass in running order (see no. 2 above). If the maximum permissible value for the optional equipment of (in the example) 325 kg is almost or completely exhausted, an upward weight deviation can therefore result in the minimum pay-mass of 100 kg being met mathematically using the default value for the mass in running order, although in fact there is no corresponding load capacity. Here, too, an example calculation for a vehicle with four seats, whose real weighed mass in running order is 2 % above the nominal value:

3.500 kg technically permissible maximum laden mass
- 2.907 kg real weighed mass in running order (+ 2 % compared to the stated value of 2,850 kg)
- 3\*75 kg mass of the passengers

- 325 kg optional equipment (maximum permissible value) = 43 kg actual load capacity (< minimum pay-mass of 100 kg)

In order to avoid such a situation, Dethleffs further reduces the maximum permissible weight of the total **optional equipment** that can be ordered on a model-specific basis. The limitation of **optional equipment** is intended to ensure that the **minimum pay-mass**, i.e. the legally prescribed free mass for **baggage** and retrofitted **accessories**, is actually available for the **vehicle load capacity** of the vehicles delivered by Dethleffs. Since the weight of a specific vehicle can only be determined when it is weighed at the **end of the line**, in very rare cases a situation may arise in which the **minimum pay-mass** at the **end of the line** is not guaranteed, despite this limitation of **optional equipment**. In order to guarantee the **minimum pay-mass** even in these cases, Dethleffs will check together with your **trade partner** and you before delivery of the vehicle whether, for example, the vehicle is loaded up, seats are reduced or **optional equipment** is removed.

# 6. Effects of tolerances of the mass in running order on the pay-mass

Regardless of the minimum pay-mass, you should note that unavoidable production-related fluctuations in the mass in running order – both upwards and downwards – have a mirror-image effect on the remaining load capacity: If you order our example vehicle (see no. 3. above), for example, with optional equipment with a total weight of 150 kg, the calculated pay-mass based on the default value for the mass in running order is 275 kg. The load capacity actually available may deviate from this value due to tolerances and may be higher or lower. If the mass in running or-

**der** of your vehicle is, for example, permissibly 2 % higher than stated in the sales documents, the **load capacity** is reduced from 275 kg to 218 kg:

3.500 kg technically permissible maximum laden mass

2.907 kg  $\,$  real weighed mass in running order (+ 2 % compared to the

stated value of 2,850 kg) 3\*75 kg mass of the passengers

150 kg **optional equipment** ordered for the specific vehicle

= 218 kg sactual load capacity

As a precaution to ensure that the calculated pay-mass is actually given, you should therefore take the possible and permissible tolerances for the mass in running order into account when configuring your vehicle. We also recommend that you weigh the laden motorhome on a non-automatic scale before each journey and, taking the individual weight of the passengers into account, determine whether the technically permissible maximum laden mass and the technically permissible maximum mass on the axle are observed.